

**Technical Sprays** 

# **Grease Sprays**

# Adhering Grease extra strong

### Also for underwater applications

WEICON Adhering Grease extra strong is a special lubricant and corrosion protectant even for underwater applications. It provides effective protection against aggressive fluids in maritime applications and in wet plants. Adhering Grease extra strong is suitable for rolling and sliding bearings even in mixed friction operation, for joints, levers, sliding guides, spindles, spline shafts, exposed gears, worm gears, chains and wire cables. It is suitable for all slide speeds permissible for grease lubrication.

IMPA Code

Technische Daten	
Base	Calcium soap
Odour	nearly odourless
Colour	beige
Specific properties	adheres even under water
Kinematic viscosity (40°C)	100 mm²/s
Kinematic viscosity (100°C)	9 mm²/s
Temperature resistance	-25 °C to +80 °C
Shelf life	24 mon.
Approvals / Guidelines	
ISSA Code	53.402.52

# **Processing**

Clean surfaces. For a better spray function, warm the product up to room temperature. Shake can before use until mixing pea is audible. Spray on from a distance of approx. 15 cm.

## Storage

Pressurized container. Protect from direct sunlight and temperatures above +50°C.

# Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

### **Available sizes**

10019873 Adhering Grease extra strong, 400 ml, beige 10059949 Adhering Grease extra strong, 400 ml, beige



The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the requested properties are recommended. A claim cannot be derived from them.

Spain phone +34 (0) 914 7997 34

WEICON GmbH & Co. KG phone +49 (0) 251 9322 0

450835

Italy phone +39 (0) 010 2924 871

WEICON Romania SRL phone +40 (0) 3 65 730 763

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON South East Asia Pte Ltd ne (+65) 6710 7671

WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65